

WX11 Series, Vinyl Coved Wall Base

Suggested Specifications Section 09 65 13

PART 1—GENERAL

1.01 SUMMARY

A. Coved vinyl wall base for wall protection.

1.02 SECTION INCLUDES

A. WX11, Vinyl Coved Wall Base

1.03 REFERENCES

A. American Society for Testing and Materials (ASTM)

B. Underwriters Laboratory (UL)

1.04 SYSTEM DESCRIPTION

A. Performance Requirements: Provide vinyl coved wall base that conforms to the following requirements of regulatory agencies and the quality control of Wallprotex.

1. Fire Performance Characteristics: Provide materials with a V-0 rating as tested in accordance with UL94.

2. Provide vinyl coved wall base that complies with ASTM F-1861-98 Type TV, Standard Specification for Resilient Wall Base.

1.05 SUBMITTALS

A. Product Data: Manufacturer's printed product data for each type of vinyl coved wall base specified.

B. Detail Drawings: Mounting details with the appropriate fasteners for specific substrates.

C. Samples: Verification samples of the wall base, 6" (152mm) long, in full size profiles for each product indicated.

D. Manufacturer's Installation Instruction: Printed installation instructions for the wall base.

1.06 DELIVERY, STORAGE AND HANDLING

A. Deliver materials in unopened factory packaging to the jobsite.

B. Inspect materials at time of delivery to assure that specified products have been received.

C. Store in original packaging in a climate controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

A. Environmental Requirements: Products must be installed in an interior climate controlled environment of 65 to 75° F.

1.08 WARRANTY

A. Standard Wallprotex limited lifetime warranty against material and manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURER

A. Acceptable Manufacturer: Wallprotex, 3750 Ohio Ave., St. Charles, IL 60174, Phone: 877-880-8115, Fax: 630-443-8930, www.wallprotex.com

B. Substitutions: Not permitted.

C. Provide all vinyl base cove and wall protection from a single source.

D. All products are to be manufactured in the USA.

2.02 MANUFACTURED UNITS

A. WX11 Series, Vinyl Coved Wall Base

1. Thickness: .080" (2mm)

2. Height: 4" (102mm)

3. Length: 60' (18.29m)

4. Finish: Satin

5. Style: Coved

2.03 MATERIALS

A. Vinyl: Wall base shall be extruded from chemical and stain resistant flexible polyvinyl chloride. A minimum of 50% post consumer recycled content is required.

2.04 FINISHES

A. Color of the wall base to be selected by the architect from the Wallprotex color selection. Surface shall have a smooth satin finish.

PART 3 - EXECUTION

3.01 EXAMINATION

A. Examine areas and conditions in which the wall base will be installed.

1. Complete all finishing operations, including painting, before beginning installation of the wall base.

B. Wall surface shall be dry and free from dirt, dust, grease, and loose paint.

3.02 PREPARATION

A. General: Prior to installation of the corner guard system, clean substrate to remove dust, debris, and loose particles.

3.03 INSTALLATION

A. General: Locate wall base as indicated on the approved detail drawing for the appropriate substrate. Install wall base level, plump, and at the height indicated on the appropriate drawing, with surfaces free from distortion or other defects in appearance.

B. Install all wall base in accordance and compliance with Wallprotex installation instructions.

3.04 CLEANING

A. At completion of the installation, clean surfaces in accordance with the Wallprotex clean-up and maintenance instructions.