

WX12 Series, Paintable Textured Vinyl Corner Guard

Suggested Specifications Section 10 26 00

PART 1—GENERAL

1.01 SUMMARY

A. Corner guard system for wall protection and decoration.

1.02 SECTION INCLUDES

A. WX12 Series Paintable Textured Vinyl Corner Guard

1.03 REFERENCES

A. American National Standard Institute (ANSI)

B. American Society for Testing and Materials (ASTM)

C. Underwriters Laboratory (UL)

1.04 SYSTEM DESCRIPTION

A. Performance Requirements: Provide wall guard systems that conform to the following requirements of regulatory agencies and the quality control of Wallprotex.

1. Fire Performance Characteristics: Provide materials with V-0 rating as tested in accordance with UL94.
2. Impact Strength: Provide Rigid vinyl profile materials that have an Impact Strength value of 19 as tested in accordance with the procedures specified in ASTM D-256, Impact Resistance of Plastics.
3. Chemical and Stain Resistance: Provide corner guards that show resistance to stain when tested in accordance with applicable provisions of ASTM D-543.
6. Fungal and Bacterial Resistance: Provide rigid vinyl that does not support fungal or bacterial growth as tested in accordance with ASTM G-21 and ASTM G-22.

1.05 SUBMITTALS

- A. Product Data: Manufacturer's printed product data for each type of corner guard specified.
- B. Detail Drawings: Mounting details with the appropriate fasteners for specific substrates.
- C. Samples: Verification samples of the corner guard, 8" (203mm) long, in full size profiles for each product indicated.
- D. Manufacturer's Installation Instruction: Printed installation instructions for each corner guard.

1.06 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite.
- B. Inspect materials at time of delivery to assure that specified products have been received.
- C. Store in original packaging in a climate controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

A. Environmental Requirements: Products must be installed in an interior climate controlled environment of 65 to 75° F.

1.08 WARRANTY

A. Standard Wallprotex limited lifetime warranty against material and manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURER

A. Acceptable Manufacturer: Wallprotex, 3750 Ohio Ave., St. Charles, IL 60174, Phone: 877-880-8115, Fax: 630-443-8930, www.wallprotex.com

B. Substitutions: Not permitted.

C. Provide all corner guards and wall protection from a single source.

D. All products are to be manufactured in the USA.

2.02 MANUFACTURED UNITS

A. Corner Guard Profile

1. WX12 Series Paintable Textured Vinyl Corner Guard Options
Size Thickness Shape

3/4" (19mm) x 3/4" (19mm), .050" (1.3mm), 90°
1-1/8" (29mm) x 1-1/8" (29mm), .075" (1.9mm), 90°

2. Standard Heights: 4 and 8 foot.

2.03 MATERIALS

A. Vinyl: Corner guard shall be extruded from chemical and stain resistant polyvinyl chloride. No plasticizers shall be added (plasticizers may aid in bacterial growth). A minimum of 50% post consumer recycled content is required.

B. The corner guard will be surface treated for the highest ASTM rating for paint adhesion.

2.04 COMPONENTS

A. Provide vinyl corner guards with self adhesive backing.

2.05 FINISHES

A. Surface shall have an orange peel texture.

PART 3 - EXECUTION

3.01 EXAMINATION

A. Examine areas and conditions in which the corner guard systems will be installed.

1. Complete all finishing operations, including painting, before beginning installation of the corner guard system.

B. Wall surface shall be dry and free from dirt, dust, grease, and loose paint.

3.02 PREPARATION

A. General: Prior to installation of corner guard system, clean substrate to remove dust, debris, and loose particles.

3.03 INSTALLATION

A. General: Locate corner guard as indicated on the approved detail drawing for the appropriate substrate. Install wall guard level, plump, and at the height indicated on the appropriate drawing, with surfaces free from distortion or other defects in appearance.

B. Install all corner guard systems in accordance and compliance with Wallprotex installation instructions.

3.04 CLEANING

A. At completion of the installation, clean surfaces in accordance with the Wallprotex clean-up and maintenance instructions.